

GUARDIAN G2 EMERGENCY LIGHT



PRODUCT DETAILS:



- Rated life: L70/B50 50000hrs
- LED: CCT 4000K, CRI>80
- Driver: Integral
- Rating: IP20, Class II
- Operating temperature: 0°C to +40°C
- Housing: Polycarbonate, Twin adjustable LED head
- Finishing: White
- Diffuser/Lens: Polycarbonate, Clear, Prismatic
- Emergency: Non-maintained, Standard/DALI version, Replaceable lithium iron phosphate (LiFeP04) battery, 18 months shelf life, Manual test, Self-test if not connected to DALI network with 'health' status reported by bicolour LED indicator (DALI version only)
- Certification: Compliant to AS/NZS2293
- Warranty: 5 years on fixture and lamp, 4 years on the battery

MADE TO ORDER OPTIONS:

IP65 enclosure white

APPLICATIONS:

Surface mount, Internal
Retail, Public auditoriums, Warehouse facilities, Factories, Airports,
School Halls



CODE	DESCRIPTION	POWER [~]	LUMENS*	EFFICACY	WEIGHT
GRLED7FL-L	2X2W 4000K CRI>80 NON-MAINTAINED WHITE	2X2W	2x306lm	153lm/W	1.0kg
FLDLED7FL-L	2X2W 4000K CRI>80 NON-MAINTAINED DALI WHITE	2X2W	2x306lm	153lm/W	1.0kg
GRWPENCL	IP65 ENCLOSURE WHITE				

*Delivered lumens from luminaire, including thermal, electrical and optic losses. [~]Tested system powers from luminaire.