

STREAMLINE BATTEN

PRODUCT DETAILS

Size: 4ft/1200mm, 5ft/1500mm
 Rated life: L70 B50 50000hrs
 LED: 4000K, CRI80, 5SDCM
 Beam angle: Symmetrical, 120°
 Glare control: UGR19 design
 Driver: Integral, Non-Dim/DALI dimming, Flicker-Free design for DALI
 Rating: IP20, Class I
 Operating temperature: 0°C to +40°C
 Housing: Cold rolled steel
 Finishing: White RAL9016, Powder coated
 Diffuser/Lens: Polycarbonate (PC), Frosted, Reeded
 Connection: Ø20mm knockout for conduit or cable glands from end or rear, Center cable entry, End to end mounting
 Warranty: 5 year





MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Other dimming options, Emergency, Suspension kit

APPLICATIONS

Surface mounted (ceiling/wall), Internal
 Schools, Libraries, Offices



| VERSION | L (MM) | W (MM) | D (MM) |
|------------|--------|--------|--------|
| 4FT/1200MM | 1166 | 170 | 79 |
| 5FT/1500MM | 1466 | 170 | 79 |

| CODE | DESCRIPTION | POWER [~] | LUMENS* | EFFICACY | WEIGHT |
|---------------|--|--------------------|---------|----------|--------|
| STMLED4/4 | STREAMLINE BATTEN 4FT/1200MM 40W 4000K CRI80 NON-DIM | 42W | 4545LM | 108LM/W | 2.2KG |
| STMLEDPRO4/4D | STREAMLINE BATTEN 4FT/1200MM 40W 4000K CRI80 DALI | 42W | 4545LM | 108LM/W | 2.2KG |
| STMLED5/4 | STREAMLINE BATTEN 5FT/1500MM 60W 4000K CRI80 NON-DIM | 61W | 6730LM | 110LM/W | 2.7KG |
| STMLEDPRO5/4D | STREAMLINE BATTEN 5FT/1500MM 60W 4000K CRI80 DALI | 61W | 6730LM | 110LM/W | 2.7KG |

[~]Tested system powers from luminaire. ^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. [^]Figures are interpolated / extrapolated from data at other versions.