



## STELLAR LED LOWBAY

### PRODUCT DETAILS:


- Rated life: L70/B50 50000hrs
- LED: CCT 4000K/5700K, CRI>80, 5 SDCM
- Driver: MeanWell, Integral, Non-Dim
- Rating: IP65, Class I
- Operating temperature: -20°C to +40°C
- Housing: Cold rolled steel
- Finishing: White
- Diffuser: Acrylic, Clear, Prismatic, Fully gasketed, Secured with stainless steel screws
- Connection: Center cable entry with M20 gland
- Warranty: 5 year

### MADE TO ORDER OPTIONS:

DALI/1-10V dimming, LED retrofit kit

### APPLICATIONS:

Surface mount, Recessed, Internal, External  
Food processing areas, Service station canopies, Retail spaces,  
Manufacturing facilities, Cold storage and Refrigerated warehouses



CODE	DESCRIPTION	POWER <sup>~</sup>	LUMENS <sup>*</sup>	EFFICACY	WEIGHT
STSLED190/84GP	SURFACE MOUNT 190W 4000K CRI>80 NON-DIM	184W	25289lm	137lm/W	11.2kg
STSLED190/85GP	SURFACE MOUNT 190W 5700K CRI>80 NON-DIM	184W	25289lm <sup>^</sup>	137lm/W <sup>^</sup>	11.2kg
STRLED190/84GP	RECESSED 190W 4000K CRI>80 NON-DIM	184W	25289lm	137lm/W	10.5kg
STRLED190/85GP	RECESSED 190W 5700K CRI>80 NON-DIM	184W	25289lm <sup>^</sup>	137lm/W <sup>^</sup>	10.5kg
STRETLED190/84	RETROFIT KIT 190W 4000K CRI>80 NON-DIM	184W	25289lm <sup>^</sup>	137lm/W <sup>^</sup>	3.3kg
STRETLED190/85	RETROFIT KIT 190W 5700K CRI>80 NON-DIM	184W	25289lm <sup>^</sup>	137lm/W <sup>^</sup>	3.3kg

\*Delivered lumens from luminaire, including thermal, electrical and optic losses. <sup>~</sup>Tested system powers from luminaire.

<sup>^</sup>Figures are interpolated / extrapolated from data at other versions.