

PIERLUX DALI HIGHBAY






PRODUCT DETAILS

Rated life: L70 B50 54000hrs
 LED: 4000K, CRI80, 6SDCM
 Beam angle: Symmetrical, 115°
 Driver: Integral, DALI dimming
 Rating: IP65, IK08, Class I
 Operating temperature: -25°C to +50°C
 Housing: Die-cast LM6 aluminium (copper content <0.1%)
 Finishing: Black, Powder coated
 Diffuser/Lens: Polycarbonate (PC), Clear
 Connection: Flex & Plug, DALI cable, Safety wire
 Accessory (order separately): DALI dimmer, Polycarbonate refractor,
 Polycarbonate refractor lens, Aluminium reflector
 Warranty: 5 year



APPLICATIONS:

Suspended (ceiling), Internal/External
 Warehousing, Industrial facilities, Workshops, Retail environments,
 Cold storage, Sports facilities





CODE	DESCRIPTION	POWER [~]	LUMENS*	EFFICACY	WEIGHT
PLHB200D4	PIERLUX DALI HIGHBAY 200W 4000K CRI80 DALI	204W	30002LM	147LM/W	4.0KG

[~]Tested system powers from luminaire. *Delivered lumens from luminaire, including thermal, electrical and optic losses. ^Figures are interpolated / extrapolated from data at other versions.



CODE: ECOHBG5PCREF **0.6KG**
POLYCARBONATE REFRACTOR



CODE: ECOHBG5ALREF **1.0KG**
ALUMINIUM REFLECTOR