

FIREFLY G2 EMERGENCY LIGHT



PRODUCT DETAILS:



- Rated life: L70/B50 50000hrs
- Driver: Integral
- Rating: IP20, Class II
- Operating temperature: 0°C to +40°C
- Housing: Polycarbonate
- Finishing: White/Black
- Emergency: Non-maintained, Replaceable lithium iron phosphate (LiFeP04) battery, 18 months shelf life, Manual test
- Certification: D32 emergency classification, Compliant to AS/NZS2293
- Connection: Complete with 1.5m 2-Pin Flex & Plug
- Warranty: 5 years on fixture and lamp, 4 years on the battery

MADE TO ORDER OPTIONS:

Vandal-proof kit (Recessed versions only)

APPLICATIONS:

Recessed/Surface mount, Internal
Office spaces, Fire passages, Retail centres, Aged care, Hospitality, Correctional facilities



CODE	DESCRIPTION	POWER [~]	LUMENS [*]	EFFICACY	WEIGHT
FFRLED2	2W D32 NON-MAINTAINED WHITE	2W	174lm	87lm/W	0.5kg
FFRLEDK2	2W D32 NON-MAINTAINED BLACK	2W	174lm	87lm/W	0.5kg
FFSLEDKITWH	SURFACE MOUNT KIT WHITE				
FFSLEDKITBK	SURFACE MOUNT KIT BLACK				
FFLEDVK	VANDAL-PROOF KIT (RECESSED VERSIONS ONLY)				

*Delivered lumens from luminaire, including thermal, electrical and optic losses. [~]Tested system powers from luminaire.