

**COLOUR SELECT**

**SHADOW ECO 100-200W FLOODLIGHT**





**PRODUCT DETAILS**

Rated life: L70 B50 54000hrs  
 LED: Colour Select 3000K/4000K/5000K, CRI80, 6SDCM  
 Beam angle: Symmetrical, 110°  
 Driver: Integral, Non dimmable  
 Rating: IP65, IK08, Class I  
 Operating temperature: -10°C to +40°C  
 Housing: LM6 Aluminium (copper content <0.1%)  
 Finishing: Black, Powder coated  
 Diffuser/Lens: Glass, Frosted  
 Connection: 1.0m Flex  
 Accessory: Complete with Trunion arm  
 Warranty\*: 5 year

**APPLICATIONS**

Surface mounted (ceiling/wall), External  
 Carparks, Commercial areas, Industry areas, Security lighting



VERSION	L1 (MM)	L2 (MM)	H1 (MM)	H2 (MM)	W (MM)
SHADOWECO100CS	307	339	247	322	98
SHADOWECO200CS	382	414	306	385	102

CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
SHADOWECO100CS	SHADOW ECO FLOODLIGHT 96W 3/4/5K @ 4K	96W	11600LM	121LM/W	4.20KG
SHADOWECO200CS	SHADOW ECO FLOODLIGHT 198W 3/4/5K @ 4K	198W	23700LM	120LM/W	5.72KG

\*Please refer to the warranty policy at [www.pierlite.co.nz](http://www.pierlite.co.nz); "POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.