

ROSS RECESSED

PRODUCT DETAILS:


- Rated life: L80/B10 50000hrs
- LED: CCT 3000K/4000K, CRI>80, 3 SDCM
- Beam angle: Symmetrical 70°, Symmetrical 90°, Asymmetrical, Double-Asymmetrical
- Glare control: UGR 19 capable
- Driver: Integral, Non-Dim/DALI dimming
- Rating: IP40, Class I
- Operating temperature: -20°C to +35°C
- Housing: Thermoplastic
- Finishing: White/Black
- Diffuser/Lens: PMMA, Frosted
- Accessory: Complete with steel spring fixing system
- Warranty: 5 year

MADE TO ORDER OPTIONS (lead time and MOQ may apply):


Other dimming options, Emergency

APPLICATIONS:

Recessed, Ceiling, Internal
Commercial, Retail, Offices, Schools



CUT-OUT: 596X140



CODE	DESCRIPTION	POWER [~]	LUMENS ⁺	EFFICACY	WEIGHT
4455-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM SYMMETRICAL 70° WHITE	44W	7233lm	164lm/W	2.1kg
4457-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM SYMMETRICAL 90° WHITE	44W	7237lm	164lm/W	2.1kg
4459-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM ASYMMETRICAL WHITE	44W	7246lm	165lm/W	2.1kg
4461-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM DOUBLE-ASYMMETRICAL WHITE	44W	7165lm	163lm/W	2.1kg
4456-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM SYMMETRICAL 70° BLACK	44W	7233lm	164lm/W	2.1kg
4458-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM SYMMETRICAL 90° BLACK	44W	7237lm	164lm/W	2.1kg
4460-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM ASYMMETRICAL BLACK	44W	7246lm	165lm/W	2.1kg
4462-LBN	500mA 43W 4000K CRI>80 UGR 19 NON-DIM DOUBLE-ASYMMETRICAL BLACK	44W	7165lm	163lm/W	2.1kg

*Delivered lumens from luminaire, including thermal, electrical and optic losses. [~]Tested system powers from luminaire.