



LEDSMART PHASE DIMMER

DIMMARI

PRODUCT DETAILS

IP20

Compatible with PDL Iconic (1 & 2 Gang), PDL 600, PDL Saturn Zen, Legrand Excel, Clipsal 2000 and HPM Excel XLP770 switch plates Phase dimming control for LED lamps and light fixtures Excellent compatibility with other lamps such as incandescent lamps, 12V halogen (dichroic) lamps/ transformers and CFL's 2W - 400W load

Configurable minimum brightness with mechanical adjustment Minimum brightness typically 0%


Separately switched 2-wire design, no neutral wire connection required for wall plate retrofit installation

Integrated LED indicator illuminates the dimmer knob Incorporates a thermal fuse to protect itself against overheating Incorporates filtering to reduce load brightness variation under conditions of line voltage ripple signal injection

"Soft-start" to help prolong the lamp and driver life Inherent immunity to installation wiring short circuit fault Warranty*: 2 year

APPLICATIONS

Surface mounted (wall), Internal Commercial, Public areas, Hotels, Garages, Schools, Health care



CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
MEDM-KIT	ROTARY PHASE DIMMER	N/A	N/A	N/A	N/A

*Please refer to the warranty policy at www.pierlite.co.nz; "POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.



0508 743 757

