















ORION ECO LED OYSTER

PRODUCT DETAILS:


- Size: Ø300, Ø350
- · Rated life: L70/B50 36000hrs
- LED: Colour Select via DIP Switch, CCT 3000K/4000K/6000K, CRI>80, 7 SDCM
- Beam angle: Symmetrical, 100°
- · Driver: Integral, Phase dimming
- · Rating: IP54, Class II
- Operating temperature: -10°C to +40°C
- · Housing: Steel base, Polycarbonate removable trim
- Finishing: White RAL9016, Powder coating
- · Diffuser: Polycarbonate, Frosted
- · Warranty: 5 year

MADE TO ORDER OPTIONS:


Integral HF motion sensor

APPLICATIONS:

Surface mount, Internal Residential, Commercial spaces



VERSION W (MM) H (MM)	



CODE	DESCRIPTION	POWER"	LUMENS*	EFFICACY	WEIGHT
ORN16W3/4/6KD	Ø300 16W COLOUR SELECT 3000K/4000K/6000K CRI>80 PHASE-DIM	16W	1316lm^	82lm/W	0.5kg
ORN23W3/4/6KD	Ø350 23W COLOUR SELECT 3000K/4000K/6000K CRI>80 PHASE-DIM	23W	1963lm^	85lm/W	0.6kg

^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. "Tested system powers from luminaire. ^@4000K.



16W

23W

Ø300

Ø350

85



