



PATHFINDER WEATHERPROOF EMERGENCY LIGHT GEN2




PRODUCT DETAILS

Rated life: L70 B10 50000hrs
 Driver: Integral, Non-Dim
 Rating: IP66, IK10, Class I
 Operating temperature: 0°C to +50°C
 Housing: Die-cast aluminium, Removable gear tray
 Finishing: Grey, Powder coated
 Diff user/Lens: Polycarbonate (PC), Clear
 Connection: 1.5m flying lead
 Accessory: Complete with surface mount brackets
 Emergency: Non-Maintained, DALI emergency (self-test if not connected to DALI), Replaceable lithium iron phosphate (LiFePO4) battery, 18 months shelf life
 Compliant: AS/NZS 2293, D63 emergency classification
 Warranty: 5 years on fixture and lamp, 4 years on battery

Driver: Integral, Non-Dim

APPLICATIONS

Surface mounted (ceiling), Internal/External
 Train stations, Carparks, Correctional facilities, Fire passages, Warehouses



CODE	DESCRIPTION	POWER [~]	LUMENS*	EFFICACY	WEIGHT
PFDLED-RL2-WP	PATHFINDER IP66 GEN2 D63 4W NON-MAINTAINED DALI EMERGENCY	4W	466LM	87LM/W	1.0KG

[~]Tested system powers from luminaire. ^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. [^]Figures are interpolated / extrapolated from data at other versions.