

ROMI SURFACE MOUNTED

PRODUCT DETAILS

Size: Ø350mm, Ø450mm, Ø600mm
 Rated life: L80 B10 50000hrs
 LED: 4000K, CRI80, 3SDCM
 Beam angle: Symmetrical, Direct (95°) & Indirect (100°)
 Glare control: UGR19 design
 Driver: Integral, DALI dimming, Flicker free design
 Rating: IP20, Class I
 Operating temperature: 0°C to +40°C
 Housing: Aluminium
 Finishing: White RAL9003, Powder coated
 Diffuser/Lens: Acrylic (PMMA), Frosted, Prismatic
 Warranty*: 5 year





MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Ø900mm, Black/Silver finishing, Other lumen package, Non dimmable, Other dimming technology, Casambi, Tunable white

APPLICATIONS

Surface mounted (ceiling), Internal
 Offices, Schools, Commercial interiors



CODE	DESCRIPTION	POWER™	LUMENS*	EFFICACY	WEIGHT
ROMISM350840DA	ROMI SURFACE MOUNTED 350 18W 4K DALI DIM	18W	1800LM	100LM/W	2.80KG
ROMISM450840DA	ROMI SURFACE MOUNTED 450 31W 4K DALI DIM	31W	3500LM	113LM/W	3.80KG
ROMISM600840DA	ROMI SURFACE MOUNTED 600 48W 4K DALI DIM	48W	5500LM	115LM/W	6.00KG

*Please refer to the warranty policy at www.pierlite.co.nz; "POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.