

LUMEN SELECT™



STREAMLINE ACADEMY BATTEN

PRODUCT DETAILS


- Size: 5ft/1500mm, 4ft/1200mm, 2ft/600mm
- Lumen maintenance: L80 54,000hrs (TM21 calculated @ 40°C)
- LED: 4000K, CRI90 (R9≥60), 3SDCM
- Beam angle: Symmetrical, 90°
- Glare control: UGR19 design
- Driver: Integral, Lumen Select, DALI-2, 100,000hrs driver life
- Flicker free: PstLM≤0.02, SVM≤0.07
- Rating: IP40, Class I
- Operating temperature: 0°C to +40°C
- Housing: Steel
- Finishing: White RAL9016, Powder coated
- Diffuser/Lens: Acrylic (PMMA), Micro prismatic
- Connection: Ø20mm knockout for conduit or cable glands, Center cable entry, End to end mounting, Linkable
- Accessory: Optional wire suspension kit, Clip on joining cover
- Warranty: 5 year

MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

280mm wide body, Fixed output, Other dimming options, Emergency

APPLICATIONS

Surface mounted (ceiling), Internal
Schools, Libraries, Offices



VERSION	L (MM)	W (MM)	H (MM)
5FT/1500MM	1565	205	54
4FT/1200MM	1265	205	54
2FT/600MM	665	205	54

CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
STA200LS5D4	STREAMLINE ACADEMY BATTEN 200X1500 43/51/58/69W 4K DALI DIM	43W	4800LM	111LM/W	5.3KG
		51W	5500LM	108LM/W	
		58W	6200LM	106LM/W	
		69W	7100LM	103LM/W	
STA200LS4D4	STREAMLINE ACADEMY BATTEN 200X1200 25/29/34/39W 4K DALI DIM	25W	2700LM	108LM/W	4.2KG
		29W	3100LM	106LM/W	
		34W	3600LM	105LM/W	
		39W	4100LM	104LM/W	
STA200LS2D4	STREAMLINE ACADEMY BATTEN 200X600 15/18/21/24W 4K DALI DIM	15W	1700LM	112LM/W	2.4KG
		18W	2000LM	111LM/W	
		21W	2400LM	114LM/W	
		24W	2700LM	112LM/W	
WIRESUSP/STA	STREAMLINE ACADEMY WIRE SUSPENSION KIT	N/A	N/A	N/A	N/A
STA200JBKT	STREAMLINE ACADEMY 200 CLIP ON JOINING COVER	N/A	N/A	N/A	N/A

"POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.