

**VERSO FLAT RD WALL LIGHT**

**PRODUCT DETAILS**

Rated life: L80 B10 60000hrs  
 LED: 3000K/4000K, CRI90, 3SDCM  
 Beam angle: Asymmetrical  
 Driver: Integral, Non-Dim  
 Rating: IP65, IK09, Class I  
 Operating temperature: -20°C to +35°C  
 Housing: Die-cast EN AB-44100 aluminium  
 Finishing: Dark grey, Polyester powder coated  
 Diffuser/Lens: Tempered glass, Clear, Prismatic  
 Warranty: 5 year





**MADE TO ORDER OPTIONS** (LEAD TIME AND MOQ MAY APPLY)


Light grey/White/Black/Stainless steel/Corten/Sand finishing

**APPLICATIONS**

Surface mounted/Recessed (wall), External  
 Driveways, Walkways, Stairs




SURFACE MOUNTED



57

RECESSED



CODE	DESCRIPTION	POWER <sup>~</sup>	LUMENS <sup>*</sup>	EFFICACY	WEIGHT
GH1392.BGXP300EN	VERSO FLAT SURFACE MOUNTED WALL LIGHT RD Ø140 4W 3000K CRI90 NON-DIM	4W	69LM	17LM/W	
GH1393.CAXP300EN	VERSO FLAT SURFACE MOUNTED WALL LIGHT RD Ø220 9W 3000K CRI90 NON-DIM	9W	171LM	19LM/W	
GH1394.BGXP300EN	VERSO FLAT RECESSED WALL LIGHT RD Ø140 4W 3000K CRI90 NON-DIM	4W	69LM	17LM/W	
GH1395.CAXP300EN	VERSO FLAT RECESSED WALL LIGHT RD Ø220 9W 3000K CRI90 NON-DIM	9W	171LM	19LM/W	
GH1392.BGXP400EN	VERSO FLAT SURFACE MOUNTED WALL LIGHT RD Ø140 4W 4000K CRI90 NON-DIM	4W	73LM	18LM/W	
GH1393.CAXP400EN	VERSO FLAT SURFACE MOUNTED WALL LIGHT RD Ø220 9W 4000K CRI90 NON-DIM	9W	181LM	20LM/W	
GH1394.BGXP400EN	VERSO FLAT RECESSED WALL LIGHT RD Ø140 4W 4000K CRI90 NON-DIM	4W	73LM	18LM/W	
GH1395.CAXP400EN	VERSO FLAT RECESSED WALL LIGHT RD Ø220 9W 4000K CRI90 NON-DIM	9W	181LM	20LM/W	

<sup>~</sup>Tested system powers from luminaire. <sup>\*</sup>Delivered lumens from luminaire, including thermal, electrical and optic losses. <sup>^</sup>Figures are interpolated / extrapolated from data at other versions.