

SOLARIS WALL LIGHT



PRODUCT DETAILS




Rated life: L90 B20 50000hrs
 LED: 3000K/4000K, CRI90, 3SDCM
 Beam angle: Asymmetrical
 Driver: Integral, Non-Dim, DALI dimming
 Rating: IP65, IK06, Class I
 Operating temperature: -10°C to +40°C
 Housing: Die-cast EN AB-47100 aluminium, Vertical tilt 60°
 Finishing: White, Polyester powder coated with special anti-corrosion treatment for coastal areas, Salt Spray testing (in compliance with ISO 9227 standard)
 Diffuser/Lens: Serigraphed tempered glass, Clear
 Warranty: 5 year

MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Symmetrical, Black/Grey finishing

APPLICATIONS

Surface mounted (wall), Internal/External
 Shopping malls, Retail spaces, High ceiling spaces, Facade



VERSION	W1 (MM)	W2 (MM)	L (MM)	L1 (MM)	L2 (MM)	D1 (MM)	D2 (MM)
12W	160	93	167	116	51	58	34
40W	220	126	240	160	80	65	40

CODE	DESCRIPTION	POWER [~]	LUMENS [*]	EFFICACY	WEIGHT
67966-LBC	SOLARIS WALL LIGHT 12W 3000K CRI90 NON-DIM	12W	1054LM	88LM/W	2.0KG
67966-LBN	SOLARIS WALL LIGHT 12W 4000K CRI90 NON-DIM	12W	1144LM	95LM/W	2.0KG
67966-LBC-DA	SOLARIS WALL LIGHT 12W 3000K CRI90 DALI	12W	1054LM	88LM/W	2.0KG
67966-LBN-DA	SOLARIS WALL LIGHT 12W 4000K CRI90 DALI	12W	1144LM	95LM/W	2.0KG
67950-LBC	SOLARIS WALL LIGHT 40W 3000K CRI90 NON-DIM	40W	4999LM	125LM/W	3.0KG
67950-LBN	SOLARIS WALL LIGHT 40W 4000K CRI90 NON-DIM	40W	5396LM	135LM/W	3.0KG
67950-LBC-DA	SOLARIS WALL LIGHT 40W 3000K CRI90 DALI	40W	4999LM	125LM/W	3.0KG
67950-LBN-DA	SOLARIS WALL LIGHT 40W 4000K CRI90 DALI	40W	5396LM	135LM/W	3.0KG

[~]Tested system powers from luminaire. ^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. [^]Figures are interpolated / extrapolated from data at other versions.