

COLOUR SELECT



POLO BULKHEAD GEN2

PRODUCT DETAILS



Size: Ø350mm, Ø430mm
 Rated life: L70 B50 54000hrs
 LED: Colour Select 3000K/4000K/5700K, CRI80, 6SDCM
 Beam angle: Symmetrical, 120°
 Driver: Integral, Non dimmable
 Rating: IP65, IK08, Class II
 Operating temperature: -20°C to +40°C
 Housing: Polycarbonate (PC)
 Finishing: White
 Diffuser/Lens: Polycarbonate (PC), Frosted
 Connection: PG9/Ø16mm cable gland, Back entry/Side entry
 Warranty*: 5 year

MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Dimming, Emergency (compliant to AS/NZS 2293), Sensor

APPLICATIONS

Surface mounted (ceiling/wall), Internal/External
 Commercial, Industrial, Residential, Apartments



CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
POLO2-14W	POLO BULKHEAD 350 14W 3/4/57K @ 3K	14W	1300LM	93LM/W	1.50KG
POLO2-21W	POLO BULKHEAD 430 22W 3/4/57K @ 3K	22W	2100LM	95LM/W	2.00KG

*Please refer to the warranty policy at www.pierlite.co.nz; "POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.