

ECO LED LINEAR HIGHBAY



PRODUCT DETAILS:

- Rated life: L80/B10 60000hrs @55°C
- LED: CCT 4000K, CRI>80, 3 SDCM
- Beam angle: Symmetrical, 120°
- Driver: Integral, Non-Dim
- Rating: IP40, Class I
- Operating temperature: -20°C to +55°C
- Housing: Cold rolled steel
- Finishing: White RAL9016, Powder coating
- Diffuser/Lens: Polycarbonate, Frosted
- Connection: 3m Flex & Plug
- Warranty: 5 year
- Accessory: Suspension kit, Acrylic lens cover, Wire guard



APPLICATIONS:

Suspended, Internal
Warehousing, Industrial facilities, Workshops, Retail environments



VERSION	L (MM)	W (MM)	H (MM)
160W	1215	285	100
240W	1215	410	100

CODE	DESCRIPTION	POWER [~]	LUMENS [*]	EFFICACY	WEIGHT
LEDHBAY160/4K	160W 4000K CRI>80 NON-DIM	157W	14381lm	92lm/W	6.7kg
LEDHBAY240/4K	240W 4000K CRI>80 NON-DIM	236W	21736lm	92lm/W	9.6kg
LHB-SUSP	SUSPENSION KIT				
LEDHB160LENS	ACRYLIC LENS COVER FOR 160W				
LEDHB240LENS	ACRYLIC LENS COVER FOR 240W				
LEDHB160WG	WIRE GUARD FOR 160W				
LEDHB240WG	WIRE GUARD FOR 240W				

*Delivered lumens from luminaire, including thermal, electrical and optic losses. [~]Tested system powers from luminaire.